

Nuvo® P200 Player

Allowing for both wired and wireless setup, the P200 player provides the ultimate installation flexibility while delivering 120 watts of high-fidelity audio from a near-infinite selection of streaming music to a single zone. Ideal for reaching hard-to-wire rooms and easily expanding Player Portfolio systems, this player blends performance and flexibility like never before.



- High-fidelity audio is delivered to every area of your home, and kept perfectly in sync.
- Compatible with Legrand's other Nuvo Player Portfolio products for a truly custom, easily expandable system (up to sixteen zones).
- Supports both wired ethernet and wireless 802.11n configuration options adding flexibility for any home.
- Includes 802.11n wireless capability and utilizes both 2.4 and 5 Ghz bands, for fast signals and broad coverage.
- All your favorite music is right at your fingertips with easy access to networked computers, streaming Internet Radio, and even audio content stored on any Android or iOS device.
- Connect to storage devices, analog equipment, or home theater receivers through the unit's audio line-in, line-out, or USB ports.
- Connect any Bluetooth device wirelessly, streaming audio from apps and services on your personal device throughout your system.
- Manage your music via the convenient wall-mounted P10 keypad or wirelessly from the palm of your hand with free apps for your Apple or Android device.

Streaming services subject to geographic availability.

Nuvo® P200 Player

Input/Output Connectors

Line Input 1 - TRS 3.5 mm stereo jack
Line Output 1 - TRS 3.5 mm stereo jack

Speaker Output 4 - Gold 5-way binding post

USB 2.0 Connection (Type A)1 Local Area Network (LAN)1 - RJ45

Supported Audio Formats

Music File (via USB or network) MP3

WMA AAC

Ogg Vorbis FLAC

WAV

Internet Radio: Pandora

Sirius/XM Rhapsody iHeart Radio

> Spotify TuneIn

> > Deezer Napster

IP Control Apple iTouch®

Apple iPhone®

Apple iPad®

Android Mobile Android Tablet

Network Connectivity

LAN (Wired Connection) 10/100base-t Ethernet Wireless Connection MIMO, 2 TX + 2 RX Channels

IEEE 802.11a/b/g/n

65 +

Wi-Fi Alliance CERTIFIED™

Amplifier Output

Damping Factor

Rated Output Power (8 ohm)120W (60W x 2)Two channels driven 20 Hz20 KHz @ 0.5% distortionRated Output Power (4 ohm)120W (60W x 2)Two channels driven 20 Hz20 KHz @ 0.5% distortion

Rated Distortion (1/2 Power) 0.20%

 Speaker Impedance
 4 – 8 ohms

 Frequency Response (20 - 20kHz)
 +/-0.5 dB

Signal-to-Noise Ratio at rated output 92 dB A – weighted

SPECIFICATIONS

Line Output:

Output Level 0-1000 mV RMS
Output Impedance 5 Ohms
Signal-to-Noise Ratio at rated output 88 dB A – weighted

Line Input:

Input Impedance 10 KOhms Input Overload 2.3 V RMS

Audio Processing

Bass Equalization +/-12 dB range
Treble Equalization +/-12 dB range

Balance

Regulatory Approvals

Safety cTUVus, CE-LVD EMC FCC, IC, CE-EMC, C-Tick Environmental Compliance RoHS

Power Requirements

Input Voltage 100 – 240VAC, 50/60 Hz Power Consumption (max) 150 W Power Consumption (typical – 1/8 audio power) 31 W

Operating Temperature 0° C to 40° C

Physical Specifications

 Unit Size (mm)
 43 H x 247 W x 175 D

 Unit Size (inch)
 1.69 H x 9.72 W x 6.89 D

 Unit Weight (kg)
 1.20

 Unit Weight (pounds)
 2.65

Shipping Specifications

 Unit Size (mm)
 360 L x 240 W x 66 H

 Unit Size (inch)
 14.17 L x 9.45 W x 2.60 H

 Unit Weight (kg)
 2.00

 Unit Weight (pounds)
 4.41

Languages Supported English, Spanish, French

Portuguese, German, Italian

Legrand reserves the right to change specifications without notice. \\

designed to be better™

